

Hex Drive



T-Star





Grade 5



hardened steel, synthetic coating

coating colors:

 high corrosion resistant

 zinc

| Diameter | Shear Strenght in lbs* | Diameter | Shear Strenght in lbs* | Diameter | Shear Strenght in lbs* |
|--------------|---------------------------|---------------|---------------------------|-----------|---------------------------|
| 1/4 x 2" | 750 | 5/16 x 3" | 830 | 1/2 x 5" | 1.650 |
| 1/4 x 2" | 750 | 5/16 x 3-1/2" | 850 | 1/2 x 6" | 1.750 |
| 1/4 x 2-1/2" | 750 | 5/16 x 4" | 1.100 | 1/2 x 8" | 1.890 |
| 1/4 x 3" | 750 | | | 1/2 x 10" | 1.950 |
| 1/4 x 3" | 750 | 3/8 x 5" | 1.200 | 1/2 x 12" | 1.950 |
| 1/4 x 3-1/2" | 770 | 3/8 x 6" | 1.260 | | |
| 1/4 x 4" | 800 | 3/8 x 8" | 1.350 | | |
| 1/4 x 4-1/2" | 800 | | | | |
| 1/4 x 5" | 820 | | | | |
| 1/4 x 6" | 840 | | | | |

***SPAX®** Lags have a patented thread design and **do not require pre-drilling**. The green coating is used for outside applications. The zinc coating is used for inside applications. 25 % of shear load is recommended as a safe work load.